

Applicant : Kenichiro Kobayashi  
Appln. No. : 09/838,905  
Page : 2

In the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1-3. (canceled)

4. (currently amended) ~~The apparatus as defined in claim 3~~ A lensless apparatus for measuring the amount which an object to be measured has moved in a plane and back and forth using a granular speck pattern generated by a reflecting laser beam, said apparatus comprising:  
a laser projector to generate a granular speck pattern corresponding to a rough surface of an object to be measured;  
a line sensor to directly pick up without a lens said granular speck pattern used as an index;  
an A/D converter coupled to said line sensor to convert an analog signal supplied from said line sensor to a digital signal;  
a processing unit coupled to the A/D converter to calculate the amount of movement of said object toward and away from said sensor on the basis of movement of the granular speck in said pattern with respect to a change in the pixel interval of said granular speck pattern picked up by said line sensor and represented by said A/D converted signal;  
a display coupled to said processing unit to display the amount of movement calculated by said processing unit; and  
a light shield positioned in front of said line sensor;  
wherein said light shield comprises a tube.

5. (original) The apparatus as defined in claim 4 wherein said tube is cylindrical.

6-9. (canceled)

Applicant : Kenichiro Kobayashi  
Appln. No. : 09/838,905  
Page : 3

10. (currently amended) ~~The apparatus as defined in claim 9~~ A lensless apparatus for measuring the amount which an object to be measured has moved using a granular speck pattern generated by a reflecting laser beam, said apparatus comprising:

a laser source for generating a granular speck pattern corresponding to a rough surface of an object to be measured;

a line sensor positioned to detect directly without a lens said granular speck pattern as an index;

a processing unit coupled to said line sensor to calculate the amount of movement of said object on the basis of movement of a granular speck in said granular speck pattern with respect to a pixel interval of said granular speck pattern detected by said line sensor;

a display coupled to said processing unit to display the amount of movement calculated by said processing unit; and

a light shield positioned in front of said line sensor;

wherein said light shield comprises a tube.

11. (original) The apparatus as defined in claim 10 wherein said tube is cylindrical.

12-15. (canceled)

16. (currently amended) ~~The apparatus as defined in claim 15~~ A lensless apparatus for measuring the amount which an object to be measured has moved in a plane and back and forth using a granular speck pattern generated by a reflecting laser beam, said apparatus comprising:

a collimated light source for generating a granular speck pattern corresponding to the surface of an object to be measured;

a line sensor positioned to detect directly without a lens said granular speck pattern as an index; and

an electrical circuit coupled to said line sensor for calculating the amount of movement of said object on the basis of movement of the granular speck in said pattern with respect to a

Applicant : Kenichiro Kobayashi  
Appln. No. : 09/838,905  
Page : 4

pixel interval of said granular speck pattern picked up by said line sensor and displaying the amount of movement calculated by said electrical circuit;

wherein said collimated light source is a laser;

further including a light shield positioned in front of said line sensor, wherein said light shield comprises a tube.

17. (original) The apparatus as defined in claim 16 wherein said tube is cylindrical.

18-49. (canceled)